

BATTERY-3

Wireless Battery Pack

IP68 | Digital wireless, 2.4G / 5.8G per model

Rated capacity **Charging input** **Discharge mode** **Light load protection**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- **Rated capacity:** **20000mAh / 3.7V**; battery power **74Wh**
- **Charging input:** TYPE-C interface 5V/2A
- **Discharge mode:** 12V constant voltage output, maximum current 1000mA
- Equipped with **5521 interface DC double-ended cable**, compatible with 5V and 12V output
- Connect the device and press the switch, the white indicator light will be on = normal output; **Click twice to force the output to turn off**
- The white indicator light goes out when the battery is exhausted

TECHNICAL SPECIFICATION

Current	20000 mA
Power Supply	Charging voltage: DC5V/2A Type-C
Waterproof Rating	IP68
Transmission	Digital wireless, 2.4G / 5.8G per model
Range	Open area 100-200 m depending on model
Latency	Low-latency real-time video
Ordering	Full parameter sheet available on request

ORDERING REFERENCE / AVAILABLE VARIANTS

Remotely off/on, waterproof magnetic power bank,work over 22 hours Battery capacity: 20000mA Charging voltage: DC5V/2A Type-C Output voltage: USB-5V and DC-5521-12V Waterproof grade: IP68

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- 4 battery indicator lights show the charging status. All lights indicate full charge
- **Light load protection:** When the load current is lower than 50mA for 15s, the internal circuit automatically turns off the output (power saving
- Wireless camera / wireless package (no wiring) power supply
- Temporary installation, demonstration, exhibition power supply

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications









TYPICAL APPLICATIONS

Trailers & Semi-Trailers | Forklifts | Reversing & Docking | Construction & Mining | Agricultural Machinery

CUSTOMISATION AVAILABLE

- **Kit content:** camera, transmitter, receiver and monitor per configuration.
- Battery or vehicle powered - confirmed per order.
- Magnet or screw mounting for forklift / trailer use.
- **Range and frequency:** 2.4G / 5.8G, distance confirmed by application.
- **Branding:** neutral or customer-branded packaging.