



BATTERY-1

Wireless Battery Pack

IP68 | Digital wireless, 2.4G / 5.8G per model

Battery life

Power consumption

Installation method

Waterproof level

Working temperature -20~+70°C

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- **Battery life:** about 15 hours
- **Power consumption:** 1.2W (corresponding to the camera taking power)
- Working voltage 12-24V (adaptive to 12V / 24V models)
- Power 6W (full package external output capability)
- Specially designed for forklift cameras/wireless vehicle cameras
- **Installation method:** **Magnetic suction** (does not damage the car body and is easy to load and unload)

TECHNICAL SPECIFICATION

Power Supply	6w
Voltage	12-24v
Waterproof Rating	IP68
Current	9600 mA
Transmission	Digital wireless, 2.4G / 5.8G per model
Range	Open area 100-200 m depending on model
Latency	Low-latency real-time video
Ordering	Full parameter sheet available on request

ORDERING REFERENCE / AVAILABLE VARIANTS

waterproof magnetic power bank,work more than 15hours Battery capacity: 9600mA Charging voltage: DC5V/3A Type-C Output voltage: DC12V/1A Waterproof grade: IP68

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- **Waterproof level:** **IP68**
- Working temperature -20~+70°C
- **Battery core:** Delangneng INR18650-3200
- **The catalog includes:** UN38.3 report and summary, MSDS, 1.2 meter drop report, stacking test report
- Air/Express shipping can be provided directly

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Trailers & Semi-Trailers

Forklifts

Reversing & Docking

Construction & Mining

Agricultural Machinery

CUSTOMISATION AVAILABLE

- **Kit content:** camera, transmitter, receiver and monitor per configuration.
- Battery or vehicle powered - confirmed per order.
- Magnet or screw mounting for forklift / trailer use.
- **Range and frequency:** 2.4G / 5.8G, distance confirmed by application.
- **Branding:** neutral or customer-branded packaging.