



CAB-01S-3

Trailer Spring Coil Cable

Vehicle camera system for trucks, buses and commercial vehicles

AHD / CVBS output

OEM & ODM

12V DC input

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- Heavy-duty spring coil trailer cable kit, 4 m extended, 3ch
- **Kit:** 1 x 4 m spring cable + 0.3 m male 3ch short cable + 0.3 m female 3ch short cable (per 100 kits)
- Copper-core conductors with aluminium-foil shielding for stable video and power transmission
- Spring coil design expands and retracts - stays tidy and resists stretching between tractor and trailer
- Professional version OD 5.5 mm vs standard 4.5 mm jacket - thicker insulation and inner construction
- Male-to-female as standard, custom connectors and lengths available

TECHNICAL SPECIFICATION

Product Type	OEM-style spring coil cable (4-pin aviation)
Coil Length	Per model / made to order
Conductor	Copper core: 30 x 0.1 mm video shield + 10 x 0.12 mm each for B+, B- and audio
Shielding	Aluminium film shielding + 3 cotton threads, PE video insulation
Jacket OD	5.5 mm professional version / 4.5 mm standard
Pin Definition	1 B+ 2 B- 3 audio signal 4 video signal
Connector	4-pin aviation, male to female as standard
Application	Trucks, semi-trailers, caravans, horse floats

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Suitable for trailer truck, semi-trailer, caravan and fleet / MDVR systems
- Spring-coil cable, flexible and durable for trailer use
- AHD high-definition video output for a clear image
- Compact, durable housing designed for vehicle use
- Easy installation with standard bracket / connector

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Passenger Cars

Taxis & Ride-Hailing

Vans & Light Commercial

Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.