CAB-2-SPLIT

Camera Signal Split Cable

Vehicle camera system for trucks, buses and commercial vehicles

30 cm split cable **Multi-view display**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- **30 cm split cable:** 2 female - 1 male, splits one camera signal into two outputs
- Copper-core conductors with shielding for clear video transmission
- Plug-and-play, pre-wired connectors - no rewiring needed
- Suitable for truck, bus, trailer and fleet / MDVR systems
- **Multi-view display:** 1/2/3/4 split and full-screen modes
- AHD high-definition video output for a clear image

TECHNICAL SPECIFICATION

Product Type	30 cm split cable: 2 female - 1 male, splits one camera signal into two outputs
Conductor	Copper core with shielding for a stable video signal
Connector	4-pin aviation / RJ45 IPC per model, male to female as standard
Customisation	Length and connector combination made to order
Application	Trucks, buses, trailers and MDVR systems

IN DETAIL

Product Views & Applications

TYPICAL APPLICATIONS

Passenger Cars | Taxis & Ride-Hailing | Vans & Light Commercial | Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.