

JFD-207

The System Requires the Use of

1920 x 1080 | microSD / TF card

TF card up to 512GB **Housing**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- Single-channel dash cam with no screen: control and playback through the phone App (FinalCamX)
- Interpolated 4K (2160p) recording; front 2G3P lens with 170 degree real viewing angle
- Chipset HI-3516-610S with CV4002 image sensor
- Built-in WiFi (RTL8188FTV USB transmission) for App preview, download and sharing
- H.265 / H.264, MP4 file format; three-axis 3D G-sensor
- Loop recording; night view; time-lapse mode; parking monitoring

TECHNICAL SPECIFICATION

Resolution	1920 x 1080
Recording	Loop recording with G-sensor event lock (per model)
Storage	microSD / TF card (32 / 64 / 128 GB, per model)
Phone App	WiFi app preview, download and sharing
Power Supply	5V Type-C or 12V car charger (hardwire kit optional)

ORDERING REFERENCE / AVAILABLE VARIANTS

2k single dashcam 1296P DVR+WIFI -Chipset:MSTSCC335R -Sensor:Front:GC2083 -Display:Mobile app display/CAR DVD -Recording resolution: 1920*1080P(30fps) -Installation method: ACC\Car charger

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Collision events are locked and will not be overwritten
- App supports more than 30 languages
- TF card up to 512GB
- RTC button battery 5V / 2.5F, no supercapacitor
- **Housing:** PC + ABS high-temperature resistant, black 3M adhesive mount
- Bare unit 91 x 35 x 31 mm; net weight 450 g (whole set)

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications









TYPICAL APPLICATIONS

Fleet Telematics | Trucks & Trailers | Buses & Coaches | Taxis & Ride-Hailing | Insurance & Evidence

CUSTOMISATION AVAILABLE

- **Recording:** confirm channels (1 / 2 / 3) and resolution split (for example 4K + 1080P).
- **Storage:** microSD / TF card size (32 / 64 / 128 GB) and the recording days required.
- **Phone app:** iOS / Android app, live preview and file download - confirm language and app branding.
- **Parking mode:** G-sensor sensitivity and time-lapse parking recording (needs the matching hardwire kit).
- **Branding:** neutral or customer-branded packaging, startup screen and app name.