

JFD-215

Front Camera Sensor GC4653 400W D123 H105 V56

2.89 inch | 1 / 2 / 3 / 4 / 8 channels | temperature -20~70°C

Private-mould hot-selling model **89 inch IPS LCD screen** **Recording resolution options**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- Private-mould hot-selling model: single-channel 4K dash cam, dual 4K+1K version optional with rear camera
- CPU HI3516CV610-20S Cortex-A7 with 1T NPU computing power
- **89 inch IPS LCD screen:** on-screen display plus App display
- Front camera GC4653 400W, lens 2G4P+IR, F1.8, angle D123° / H105° / V56°
- Optional rear camera GC2083 200W, lens 2G2P, F2.0, angle D140° / H105°
- Recording resolution options: single 4K 3840x2160@30fps, dual 4K+1K, dual 2K+1K

TECHNICAL SPECIFICATION

Recording	format H.264 default /h.265 TS stream
Power Supply	supply type
Battery	RTC button battery
Video Output	Built-in microphone recording
Storage	temperature -20~70°C
Display Size	2.89 inch
Channels	1 / 2 / 3 / 4 / 8 channels (per model)
Connectivity	4G, GPS, WiFi, ADAS / DMS optional
Video Input	AHD 1080P / 720P, IPC supported

ORDERING REFERENCE / AVAILABLE VARIANTS

4k single front dashcam 1.LCD 2.89 inches 2.Front camera Sensor GC4653 400W D123 H105 V56 3.Rear camera Sensor GC2083 200W D140 H105 4.G-Sensor Built-in 3 axes 5.Speaker Wire welding, 8/1W speaker 6.Wifi 5.8GWIFI 7.supports up to 256G Exfat/fat32 8. 9.

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- 8G WiFi with the FinalCamX App (31 languages)
- Built-in GPS optional; electronic dog broadcast optional; 4G options for image / video upload and live view
- H.264 / H.265, TS stream; one-second save technology keeps the last file even on sudden power loss
- G-sensor collision lock (detectable range -16g to +16g, sensitivity 5)
- Parking monitoring and time-lapse recording (step-down cable required)
- Loop recording 1 / 3 / 5 minutes; one-key emergency recording

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications









TYPICAL APPLICATIONS

Fleet Telematics | Trucks & Trailers | Buses & Coaches | Taxis & Ride-Hailing | Insurance & Evidence

CUSTOMISATION AVAILABLE

- **Channels and camera type:** confirm 1 / 2 / 3 / 4 / 8 channels and camera model.
- **Storage:** SD card or 2TB SSD / HDD; confirm recording days required.
- **Connectivity:** 4G, GPS, WiFi, ADAS / DMS - confirmed per order.
- **Platform:** confirm whether our CMSV platform is required (license cost separate).
- **Branding:** neutral or customer-branded packaging and labels.