

JFD-51

2 Channel Battery GPS Dash Camera

/Frame 3840x2160P/30fps | 120° | GC4653 | Temperature -30~80°C

256G tf card support max | **park model function** | **stand for 90degree temperature** | **Recording quality**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- 256G tf card support max
- park model function
- stand for 90degree temperature
- 4K + 1080P dual-lens dash cam, no screen: control through the FinalCamX App
- Chipset MSTSSC8629Q, Dual CA7 1GHz, 16M flash
- Rear camera GC2083, lens 2G2P F1.8 waterproof and antifog, angle D140° / H105° / V54°, 1920x1080P@30fps with HDR

TECHNICAL SPECIFICATION

Battery	/Power supply type Port,Compatible with 5V and 12V car
Image Sensor	GC4653
Lens	Angle D123°/H105°/V56°
Resolution	/Frame 3840x2160P/30fps
Recording	time can be set, such as 12 or 24
Power Supply	Failure Protection
Storage	Temperature -30~80°C
Viewing Angle	120°
Phone App	WiFi app preview, download and sharing

ORDERING REFERENCE / AVAILABLE VARIANTS

4k 2ch dual lens wifi dashcam 1. 3840*2160 30FPS front+1080p rear 2.256G support 3.without sreen 4. only front view 5. cigarate light power 6. small battery inside buttons 7. NT 96670 cpu 8.GC4653 lens 120degree 9.with rear camera 10. | 4k 2ch wifi dashcam 1. 3840*2160 30FPS 2.256G support 3.without sreen 4. only front view 5. cigarate light power 6. small battery inside buttons 7. NT 96670 cpu

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Built-in GPS; 2.4GHz WiFi (Realtek 8189 module) for App preview, download and sharing
- **Recording quality:** 2160P / 1440P / 1080P / 720P; video encoding H.265, TS stream
- Starlight night vision; shake reduction included
- Loop recording with 1 / 3 / 5 minute segments; power-failure protection keeps the last video
- **G-sensor event lock:** files are encrypted and not overwritten
- Parking monitoring / time-lapse recording (12 or 24 hours, 1 / 2 / 5 frames per second, needs matching power hardware)

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications









TYPICAL APPLICATIONS

Fleet Telematics | Trucks & Trailers | Buses & Coaches | Taxis & Ride-Hailing | Insurance & Evidence

CUSTOMISATION AVAILABLE

- **Recording:** confirm channels (1 / 2 / 3) and resolution split (for example 4K + 1080P).
- **Storage:** microSD / TF card size (32 / 64 / 128 GB) and the recording days required.
- **Phone app:** iOS / Android app, live preview and file download - confirm language and app branding.
- **Parking mode:** G-sensor sensitivity and time-lapse parking recording (needs the matching hardwire kit).
- **Branding:** neutral or customer-branded packaging, startup screen and app name.

OPTIONS & ABOUT US

Options, Packing & Why Jifuan

PACKING & DELIVERY

- **MOQ:** flexible, from 50-100 pcs per model for standard items (mixing allowed).
- **Lead time:** 3-20 working days after deposit, depending on quantity and stock.
- **Packing:** individual white / colour box, master carton with buyer label.
- **Terms:** FOB Shenzhen; T/T, PayPal or Western Union.
- **Warranty:** 12 months from shipment against manufacturing defects.
- **Samples:** available for evaluation before mass production.

QUALITY CONTROL

- 100% ageing test before packing: every unit runs on a burn-in rack.
- **Waterproof test:** IP67 / IP68 / IP69K pressure and immersion checks on sealed models.
- High & low temperature chamber: -20C to +70C operating verification.
- Vibration and shock test for truck, bus and off-highway applications.
- **Full-function check:** video output, IR switching, connector and cable continuity.
- 1-year warranty with responsive technical support and spare-parts supply.

WHY BUY FROM JIFUAN

- **Supply chain integration:** cameras, monitors, MDVR and 360 systems matched from a vetted supplier network - one contact, one shipment.
- **Product experience:** 15+ years on vehicle video, so the platform that fits your vehicle and budget is the one we recommend.
- **Project experience:** fleet, bus, trailer and off-highway builds supplied with the brackets, cables and connectors the vehicle actually needs.
- **Customisation:** housing colour, logo, bracket, connector, cable length, lens angle and firmware changed to suit your market, with a fast answer on feasibility.

Contact us for a quotation

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

+86 188 7400 7838 (WhatsApp / WeChat) **info@jfacam.com**