JFD-W17

3 Inch 2 Channel Touch ADAS 4G GPS Dash Camera

640 x 360 | 135° | 3 inch | 2 channels

3inch touch screen **have password for setting,987456** **can check record on dashcam**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- can set server information on dashcam
- 3inch touch screen
- have password for setting,987456
- can check record on dashcam
- both app on android and iphone
- front view adas function

TECHNICAL SPECIFICATION

Resolution	640 x 360
Display Size	3 inch
Channels	2 channels
Viewing Angle	135°
Storage	128G
Power Supply	DC 12-24 V
Connectivity	4G, GPS, WiFi, ADAS / DMS optional
Video Input	AHD 1080P / 720P, IPC supported

ORDERING REFERENCE / AVAILABLE VARIANTS

- 3inch touch screen with display resolution 640*360P 4g gps 2ch dashcam without cmsv license and server cost - android 8.1 2+32G system - Dual Cams: 720P+1080P, H.264, TS video format - front is 135 degree, back is 125 degree - 4G network band: FDD LTE B1/3/4/5/7/8/12 - support GPS navigation - ADAS function (LDWS, FCWS, FVWS) - Bluetooth + WIFI spot + FM transmit+ Google Play -

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- can use car assist app free to personal use
- can use cmsv app to fleet use
- 4G mini dual-lens dash cam with 3 inch touch screen (640 x 360)
- Android 10 system; Spreadtrum SL8541E quad-core Cortex-A53 @1.4GHz, Mali820@680MHz
- Front GC2053 image sensor with 130 degree view
- Rear camera 1920 x 1080P with 120 degree view

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications

TYPICAL APPLICATIONS

Fleet Telematics | Trucks & Trailers | Buses & Coaches | Taxis & Ride-Hailing | Insurance & Evidence

CUSTOMISATION AVAILABLE

- **Channels and camera type:** confirm 1 / 2 / 3 / 4 / 8 channels and camera model.
- **Storage:** SD card or 2TB SSD / HDD; confirm recording days required.
- **Connectivity:** 4G, GPS, WiFi, ADAS / DMS - confirmed per order.
- **Platform:** confirm whether our CMSV platform is required (license cost separate).
- **Branding:** neutral or customer-branded packaging and labels.