



JFD-W18

6.3 Inch 2 Channel 4G GPS Dash Camera

640 x 360 | 6.3 inch | 2 channels | 256G

4g, gps function

free app to use

Dual-lens 4G dash cam

TF card maximum 512G

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- 4g, gps function
- free app to use
- **Dual-lens 4G dash cam:** 2K + 1080P dual recording
- 3 inch screen for local view and setup
- 4G + GPS function, free app (Cloudspirit) for personal use
- TF card maximum 512G

TECHNICAL SPECIFICATION

Channels	2 channels
Display Size	6.3 inch
Resolution	640 x 360
Power Supply	DC 9-16 V
Storage	256G
Connectivity	4G, GPS, WiFi, ADAS / DMS optional
Video Input	AHD 1080P / 720P, IPC supported

ORDERING REFERENCE / AVAILABLE VARIANTS

2CH 4g gps dashcam CAT1 WITHOUT cmsv license and server cost 1.dual lens recording 2.front is 2k and back is 1080p 4. support wifi gps tracking 5.Network:B1\B3\B5\B8\B40 6.3inch lcd screen, display resolution is 640*360p 7.fit 9-16v power supply 8. support live video check on phone via the free app 9.fit max 256g card for recording 10.support g-sensor, loop recording, parking monitor

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Front actual view angle about 100 degree, rear about 110 degree
- Compact windscreen housing with 3M adhesive mount
- Loop recording with automatic overwrite
- Available for Europe, Middle East, Russia and India markets
- Optional CMSV server / fleet platform version
- Good value entry model for cars, vans and light trucks

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Fleet Telematics

Trucks & Trailers

Buses & Coaches

Taxis & Ride-Hailing

Insurance & Evidence

CUSTOMISATION AVAILABLE

- **Channels and camera type:** confirm 1 / 2 / 3 / 4 / 8 channels and camera model.
- **Storage:** SD card or 2TB SSD / HDD; confirm recording days required.
- **Connectivity:** 4G, GPS, WiFi, ADAS / DMS - confirmed per order.
- **Platform:** confirm whether our CMSV platform is required (license cost separate).
- **Branding:** neutral or customer-branded packaging and labels.