JFD-W21

6.3 Inch Touch 4G GPS Dash Camera

640 x 360 | 135° | 6.3 inch | 1 / 2 / 3 / 4 / 8 channels

4G dual-lens mini dash cam **Storage** **Front 2K, rear 1080P@25fps** **4G bands**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- 4G dual-lens mini dash cam: 2K front + 1080P rear, with WiFi, GPS and remote monitor
- 2 inch IPS screen with 320 x 240 display resolution
- **Storage:** RAM 128MB + ROM 512MB, Linux system
- Front camera GC2063 with 135 degree view angle; rear camera GC2033 with 125 degree view angle
- Front 2K, rear 1080P@25fps
- Built-in GPS antenna; WiFi 802.11b/g/n 2.4GHz

TECHNICAL SPECIFICATION

Viewing Angle	135°
Display Size	6.3 inch
Resolution	640 x 360
Power Supply	DC 9-16 V
Storage	128G
Channels	1 / 2 / 3 / 4 / 8 channels (per model)
Connectivity	4G, GPS, WiFi, ADAS / DMS optional
Video Input	AHD 1080P / 720P, IPC supported

ORDERING REFERENCE / AVAILABLE VARIANTS

2K+1080p 4g gps dashcam CAT1 without server and cmsv 1.dual lens recording 2. front is 2k and back is 1080p 3.front is 135 degree view and rear is 125 degree 4. support wifi gps tracking 5. Network:B1\B3\B5\B8\B40 6.3inch lcd screen, display resolution is 640*360p 7.fit 9-16v power supply 8. support live video check on phone via the free app 9. fit 128g card for recording 10. support g-sensor, loop

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- **4G bands:** FDD LTE B1, B3; TDD LTE B38, B39, B40, B41
- 4G remote monitor on Android phone or iPhone via the free Cloudspirit app
- Live video check, two-way communication, remote download of video files from the TF card
- G-sensor and loop recording support
- Built-in loudspeaker and microphone
- Video format TS H.264; max TF card 128G with Class 10 or above

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications

TYPICAL APPLICATIONS

Fleet Telematics | Trucks & Trailers | Buses & Coaches | Taxis & Ride-Hailing | Insurance & Evidence

CUSTOMISATION AVAILABLE

- **Channels and camera type:** confirm 1 / 2 / 3 / 4 / 8 channels and camera model.
- **Storage:** SD card or 2TB SSD / HDD; confirm recording days required.
- **Connectivity:** 4G, GPS, WiFi, ADAS / DMS - confirmed per order.
- **Platform:** confirm whether our CMSV platform is required (license cost separate).
- **Branding:** neutral or customer-branded packaging and labels.