



JPC-101

Universal Camera

110° | AHD CMOS, 1/2.9" (2053 +8536H) | temperature: -30°C&80°C | grade: IP69

8mm lens, 110° wide view angle

Magnetic base installation

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- AHD CMOS 1/2.9" sensor (2053 + 8536H), 1080P / 720P optional
- 1920(H)*1080(V)@30fps NTSC / 1920(H)*1080(V)@25fps PAL
- 10 pcs 850nm IR LEDs - 0.1 Lux day, 0 Lux with IR
- 8 mm lens, 110 degree wide viewing angle
- Video output 1.0Vp-p / 75 ohm, AHD
- IP69 waterproof, shock resistance 4.5G

TECHNICAL SPECIFICATION

Image Sensor	AHD CMOS, 1/2.9" (2053 +8536H)
Picture Element	(optional) 720P , 100W / , 1080P ,200W
Resolving Power	(optional) 1920(H)*1080(V)@30fps NTSC/ PAL1920(H)*1080(V)@25fps
Minimum Illumination	0.1Lux(day),0Lux(with IR)
Lens	2.8mm
Viewing Angle	110°
Video Output	1.0VP-P.75 ohm
Waterproof Rating	grade: IP69
Power Supply	Voltage: DC12V
Storage	temperature: -30°C&80°C

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- DC 12V, current < 300mA, working temperature -20C to +70C
- 4-pin aviation connector as standard (RCA optional)
- For trucks, buses, vans and commercial vehicles
- 8mm lens, 110° wide view angle
- Magnetic base installation
- IP69 waterproof, 4.5G shock resistance

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- **Lens angle and mounting position:** confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- **Quantity, packing (colour box / neutral box) and printing or logo requirements.**
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.


Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Passenger Cars

Taxis & Ride-Hailing

Vans & Light Commercial

Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.