



## JPC-120-IR

### Night Vision Rear Camera for Truck

1920\*1080 | 110° | 1/2.9 CMOS | IP69K

4-pin aviation cable

Adjustable reversing guide lines

#### Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,  
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,  
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

[info@jfacam.com](mailto:info@jfacam.com)

[www.jfacam.com](http://www.jfacam.com) | [www.antuvision.com](http://www.antuvision.com)

# Key Features & Specifications

## KEY FEATURES

- White metal housing night vision rear camera for trucks
- 2053 + 8536H chipset color CMOS, 1920(H)x1080(V), AHD output
- 110 degree viewing angle, 2.8 mm lens
- IR distance 10 m with auto IR-cut, minimum illumination 0.1 Lux / F1.2
- All-aluminium alloy waterproof housing, anti-demolition design, IP69K
- Power 12V (8V-15V) < 2.5W, working temperature -20C to +70C

## TECHNICAL SPECIFICATION

|                       |                                |
|-----------------------|--------------------------------|
| Image Sensor          | 1/2.9 color CMOS               |
| DSP Chipset           | 1080p                          |
| Viewing Angle         | 110°                           |
| Pixel / Resolution    | 1920*1080                      |
| Minimum Illumination  | 0.1Lux/ F1.2                   |
| Shutter Speed         | 1/50S-1/100000S                |
| IR Distance           | 10M                            |
| IR-Cut Filter         | Auto switching (day / night)   |
| Lens                  | 2.8 mm                         |
| Video Output          | AHD                            |
| Operating Temperature | -20°C to +70°C, humidity 0-90% |
| Waterproof Rating     | IP69K                          |

## Selling Points, Ordering & Usage Notes

### PRODUCT SELLING POINTS

- **4-pin aviation cable:** 1 red 12V+ / 2 black 12V- / 4 yellow video signal
- 720P high-definition AHD video output for a clear, detailed picture
- Wide 110 degree viewing angle covers blind spots around the vehicle
- Mirror / normal image selectable to match camera position
- Adjustable reversing guide lines
- Wide 12V vehicle power input with protection

### ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

### USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

#### Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,  
Longhua District, Shenzhen, China  
*OEM & ODM welcome - custom logo, packaging, connectors,  
cable length and firmware available on request.*

**+86 188 7400 7838 (WhatsApp / WeChat)**

**info@jfacam.com**

**www.jfacam.com | www.antuvision.com**

## Product Views & Applications



### TYPICAL APPLICATIONS

Passenger Cars

Taxis & Ride-Hailing

Vans & Light Commercial

Parking Assistance

### CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.

## Options, Packing & Why Jifuan

### PACKING & DELIVERY

- **MOQ:** flexible, from 50-100 pcs per model for standard items (mixing allowed).
- **Lead time:** 3-20 working days after deposit, depending on quantity and stock.
- **Packing:** individual white / colour box, master carton with buyer label.
- **Terms:** FOB Shenzhen; T/T, PayPal or Western Union.
- **Warranty:** 12 months from shipment against manufacturing defects.
- **Samples:** available for evaluation before mass production.

### QUALITY CONTROL

- 100% ageing test before packing: every unit runs on a burn-in rack.
- **Waterproof test:** IP67 / IP68 / IP69K pressure and immersion checks on sealed models.
- High & low temperature chamber: -20C to +70C operating verification.
- Vibration and shock test for truck, bus and off-highway applications.
- **Full-function check:** video output, IR switching, connector and cable continuity.
- 1-year warranty with responsive technical support and spare-parts supply.

### WHY BUY FROM JIFUAN

- **Supply chain integration:** cameras, monitors, MDVR and 360 systems matched from a vetted supplier network - one contact, one shipment.
- **Product experience:** 15+ years on vehicle video, so the platform that fits your vehicle and budget is the one we recommend.
- **Project experience:** fleet, bus, trailer and off-highway builds supplied with the brackets, cables and connectors the vehicle actually needs.
- **Customisation:** housing colour, logo, bracket, connector, cable length, lens angle and firmware changed to suit your market, with a fast answer on feasibility.

## Contact us for a quotation

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

**+86 188 7400 7838 (WhatsApp / WeChat)**    **info@jfacam.com**