JPC-121-W

Dual-Lens Camera

Vehicle camera system for trucks, buses and commercial vehicles

AHD / CVBS output **OEM & ODM** **12V DC input**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- Dual-lens rear camera in one housing: a 110 degree wide lens plus a 60 degree narrow lens
- About 180 degree vertical coverage from the two lenses - the rear blind spot is covered with only one mounting position
- One camera / one bracket / one cable replaces two single-lens cameras - saves an installation position, a cable run and installation time
- AHD 1080P output, 1920(H)x1080(V), PAL system - clear and stable picture on AHD monitors and MDVR
- Mirror image as standard, without parking line - the picture is mirrored and no reversing guide line is drawn on it
- 2053 + 8536H chipset, 1/2.9" CMOS sensor; 0.1 Lux in daylight, 0 Lux with IR

TECHNICAL SPECIFICATION

DSP Chipset	FH8536H + GC2053 (2053 + 8536H)
Video Output	AHD / CVBS selectable, PAL & NTSC
Connector	4-pin aviation (RCA optional)
Power Supply	DC 12V standard (8-15V working range)
Housing	Metal housing, sealed against water and dust

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- 18 pcs 850 nm IR LEDs, night vision distance 15 m with auto IR-cut
- 3D-DNR / 2D-DNR digital noise reduction; video output 1.0Vp-p 75 ohm
- White housing, lens 2.8 mm / 3.6 mm; 4-pin aviation connector as standard (RCA optional)
- DC 12 V (8-15 V), current < 500 mA, working temperature -20C to +70C
- IP68 waterproof housing with 4.5G shock resistance - for trucks, trailers, buses, vans, forklifts and MDVR systems
- 720P high-definition AHD video output for a clear, detailed picture

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications

TYPICAL APPLICATIONS

Passenger Cars | Taxis & Ride-Hailing | Vans & Light Commercial | Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.