



JPC-173

Night Vision Rear Camera for Truck

1920*1080 | 110° | 1/2.9 CMOS | IP68

Full 304 stainless steel housing

Anti-corrosion

Thick tempered glass mirror

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- Full 304 stainless steel housing: The entire housing is 304 stainless steel, not an iron shell painted or an aluminum shell
- **Anti-corrosion:** Resistant to acid and alkali, salt spray, snow melting agents and chemical fertilizers, no rust at the seaside
- Impact resistance and anti-tampering: The metal housing itself is a protection, resistant to smashing and collision
- Isolation and explosion-proof design: The whole machine has an isolation structure, and the shell is separated from the circuit to prevent the device
- Thick tempered glass mirror: more impact-resistant and scratch-resistant than ordinary glass, and the mirror will not become smeared after long-term
- Small metal housing, approximately 56x52mm in size, easy to install and route cables

TECHNICAL SPECIFICATION

Image Sensor	1/2.9 color CMOS
DSP Chipset	1080p
Viewing Angle	110°
Pixel / Resolution	1920*1080
Minimum Illumination	0.1Lux/ F1.2
Shutter Speed	1/50S-1/100000S
IR Distance	10M
IR-Cut Filter	Auto switching (day / night)
Lens	2.8 mm
Video Output	AHD
Operating Temperature	-20°C to +70°C, humidity 0-90%
Waterproof Rating	IP68

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- The main body contains a heating plate: defrosting and defogging in low-temperature environments, the lens will not fog or freeze
- Adapted to cold areas, cold chains, and northern winter working conditions; ACC preheats before driving after powering on, making the picture clearer
- Heating power is about 2.5W (see the practices of similar 304 explosion-proof products)
- 1080P AHD high definition output, 1920(H)x1080(V)
- Default 2053 + 8536H scheme, 1/2.9" CMOS sensor
- Optional 720P 100W / 1080P 200W pixel version; 1920(H)x1080(V)@30fps NTSC / @25fps PAL

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.



Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Passenger Cars

Taxis & Ride-Hailing

Vans & Light Commercial

Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.

Options, Packing & Why Jifuan

PACKING & DELIVERY

- **MOQ:** flexible, from 50-100 pcs per model for standard items (mixing allowed).
- **Lead time:** 3-20 working days after deposit, depending on quantity and stock.
- **Packing:** individual white / colour box, master carton with buyer label.
- **Terms:** FOB Shenzhen; T/T, PayPal or Western Union.
- **Warranty:** 12 months from shipment against manufacturing defects.
- **Samples:** available for evaluation before mass production.

QUALITY CONTROL

- 100% ageing test before packing: every unit runs on a burn-in rack.
- **Waterproof test:** IP67 / IP68 / IP69K pressure and immersion checks on sealed models.
- High & low temperature chamber: -20C to +70C operating verification.
- Vibration and shock test for truck, bus and off-highway applications.
- **Full-function check:** video output, IR switching, connector and cable continuity.
- 1-year warranty with responsive technical support and spare-parts supply.

WHY BUY FROM JIFUAN

- **Supply chain integration:** cameras, monitors, MDVR and 360 systems matched from a vetted supplier network - one contact, one shipment.
- **Product experience:** 15+ years on vehicle video, so the platform that fits your vehicle and budget is the one we recommend.
- **Project experience:** fleet, bus, trailer and off-highway builds supplied with the brackets, cables and connectors the vehicle actually needs.
- **Customisation:** housing colour, logo, bracket, connector, cable length, lens angle and firmware changed to suit your market, with a fast answer on feasibility.

Contact us for a quotation

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

+86 188 7400 7838 (WhatsApp / WeChat) **info@jfacam.com**