



JPC-25

Brief Introduction Universal Type Car Reversing Camera

720P | IP69K

Colour black; Material plastic

Image sensor HD CCD / CMOS

Signal system PAL or NTSC

Package

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- Colour black; Material plastic
- Lens angle 110 / 170 degree options
- TV lines 420 / 480 TV Lines, 720P, 1080P
- Image sensor HD CCD / CMOS
- Signal system PAL or NTSC
- Universal for all cars; rear, front or side mounting

TECHNICAL SPECIFICATION

DSP Chipset	FH8536H + GC2053 (2053 + 8536H)
Voltage	DC 12V & 24V (optional)
Waterproof Rating	IP69K
Lens	Angle: 110/170 degree
Housing Material	Plastic
Video Output	CMOS
TV System	PAL/NSTC
Connector	RCA plug
Power Supply	12V
Resolution	720P

ORDERING REFERENCE / AVAILABLE VARIANTS

CMOS,480TVL,PAL/NSTC,RCA plug,12V ,better quality cool harness,pure copper cable | AHD,720P,PAL/NSTC,RCA plug,12V ,better quality cool harness,pure copper cable

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Waterproof IP69K with sealed lens ring
- DC 12V & 24V (optional); circuit protection function
- High definition, parking easier and safer
- Scientific design and easy installation
- **Package:** 1 x backup camera, 1 x 1 m DC power cable, 1 x 6 m AV cable, 1 x hole saw
- Standard tail cable 5 copper + 5 steel; BMW plug and pure-copper cable optional

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Passenger Cars

Taxis & Ride-Hailing

Vans & Light Commercial

Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.