



JPC-32

Flush Mount Dome Camera

720P

Flush mounted

Signal options

Package

Connector options

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- Iron clip gives a stronger, more secure hold than plastic clips
- **Flush mounted:** the lens sits almost level with the bumper for a tidy look
- Universal for all cars; rear, front or side mounting
- **Signal options:** CVBS 420/480 TV Lines, AHD 720P, AHD 1080P
- PAL or NTSC signal system; mirror image and reversing grid selectable
- Waterproof IP69K housing with sealed lens ring

TECHNICAL SPECIFICATION

DSP Chipset	FH8536H + GC2053 (2053 + 8536H)
Video Output	CMOS
TV System	PAL/NSTC
Connector	RCA plug
Power Supply	12V
Resolution	720P

ORDERING REFERENCE / AVAILABLE VARIANTS

CMOS,480TVL,PAL/NSTC,RCA plug,12V ,better quality cool harness,pure copper cable | AHD,720P,PAL/NSTC,RCA plug,12V ,better quality cool harness,pure copper cable

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- DC 12V standard, 24V optional; circuit protection function
- **Package:** 1 x camera, 1 x 1 m DC power cable, 1 x 6 m AV cable, 1 x hole saw
- Standard tail cable 5 copper + 5 steel; BMW plug and pure-copper cable optional
- 720P high-definition AHD video output for a clear, detailed picture
- Wide 12V vehicle power input with protection
- **Connector options:** RCA

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Passenger Cars

Taxis & Ride-Hailing

Vans & Light Commercial

Parking Assistance

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.