

JPM-07V

7 Inch 1 Channel VGA Monitor

TFT LCD with LED backlight

One VGA input **One AV input (CVBS)** **One HDMI input (supports 1080P)** **SD-712 platform specifications**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- **One VGA input:** connect to MDVR/vehicle host/computer
- **One AV input (CVBS):** connect to ordinary cameras and reversing cameras
- One HDMI input (supports 1080P): connect to HD player/computer/screen projection
- SD-712 platform specifications: two CVBS + one VGA + one HDMI
- 7-inch high-brightness IPS screen, 16: 9, resolution 1024 x R.G.B x 600
- **Viewing angle range:** 180° up, down, left, right, and clear from the side

TECHNICAL SPECIFICATION

Display	TFT LCD with LED backlight
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Power Supply	DC 12-36V wide voltage
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- **Light sensing function:** automatically adjusts screen brightness according to ambient light, bright enough during the day but not dazzling at night
- 1-way reverse trigger control: automatically switch the screen when the reverse gear is engaged
- **OSD menu:** image settings, mirror settings, system settings (brightness, contrast, color, language, mirror)
- Video format PAL / NTSC
- **Audio:** CVBS two audio inputs + HDMI one audio input

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications









TYPICAL APPLICATIONS

Trucks & Trailers | Buses & Coaches | Forklifts | Vans & Light Commercial | Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.