

JPM-09D-JPM09D9i

9 Inch Monitor

TFT LCD with LED backlight

Viewing range **Power supply 12-24V**

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- Resolution 1024 x R.G.B x 600, the picture is clear and delicate
- **Viewing range:** left/right 85°, up 85°, down 85°, both driver and co-pilot can see clearly
- Dimensions 172 x 115 x 24 mm (including 47 mm sunshade)
- 2-channel AHD input, automatic switching to V2 when reversing (core function)
- 2-channel AHD video input, automatically switches to V2 reversing screen when reversing
- Supports AHD 720P / 960P / 1080P, and is compatible with CVBS / TVI input (old cameras can also be connected)

TECHNICAL SPECIFICATION

Display	TFT LCD with LED backlight
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Power Supply	DC 12-36V wide voltage
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

IN DETAIL

Product Views & Applications









TYPICAL APPLICATIONS

Trucks & Trailers | Buses & Coaches | Forklifts | Vans & Light Commercial | Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.