



JPM-1016

1 AHD Truck Monitor

ratio 16:9 | temperature -30~80°C

Viewing range

PAL / NTSC auto switching

Power supply 12-36V

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- 1-inch high-definition digital screen, resolution 1024 x R.G.B x 600
- Viewing range:** 85° left and right, 85° up and down
- 2 AHD video inputs, single image display (two cameras can be connected, one of which is displayed on the screen)
- Support 720P / 960P / 1080P, compatible with CVBS / AHD
- Automatically switches to V2 when reversing, with built-in reversing reference line
- PAL / NTSC auto switching

TECHNICAL SPECIFICATION

Display	ratio 16:9
Power Supply	requirements DC 9-36V input, output 12V
Power Consumption	7W
Storage	temperature -30~80°C
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

ORDERING REFERENCE / AVAILABLE VARIANTS

QTY: 10PCS G.W: 14.95kg Size: 58.3*30.5*41CM

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- **Power supply 12-36V:** universal for 12V / 24V models
- High and low voltage protection + short circuit protection, good stability
- Working temperature -20~+70°C, storage temperature -30~+80°C
- 1-inch model body 257 x 170 x 33mm (including sunshade 82mm); headrest frame 270 x 184 x 35.5mm
- Standard metal U-shaped bracket + removable sun visor

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.


Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Trucks & Trailers

Buses & Coaches

Forklifts

Vans & Light Commercial

Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.