JPM-706S

7 Inch 2 Channel Mirror Touch Battery AI AHD Monitor

1280 x 720 | 85° | TFT LCD with LED backlight | 2 channels

Reverse trigger **PAL / NTSC auto switching** **With video recording function** **With lock button****

Shenzhen Jifuan Intelligent Technology Co., Ltd.
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)
info@jfacam.com
www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- 7-inch screen, resolution 1024 x R.G.B x 600
- 2 channels of AHD high-definition input, single-screen/two-split display switchable
- Split one screen into two and watch two cameras at the same time: rear view + side blind spots, or blind spots on the left and right sides
- **Reverse trigger:** Automatically switch to reverse screen when engaging reverse gear
- PAL / NTSC auto switching
- With video recording function: two channels of video can be recorded and stored (there are recording demonstration videos in the directory)

TECHNICAL SPECIFICATION

Viewing Angle	85°
Image Mode	Mirror image
Resolution	1280 x 720
Power Supply	High-low voltage protection & short circuit protection
Connector	RCA / 4pin connector (optional)
Channels	2 channels
Display	TFT LCD with LED backlight
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

ORDERING REFERENCE / AVAILABLE VARIANTS

7", 9", 10.1"-inch AHD dual-screen on the same display (Optional DVR recording) 1.AV Resolution: 1024R.G.B600 2.Back Light Luminance: LED, 600-700 cd/m2 3.View angle: L/R:85°, UP:85°, down:85° degree 4.Two-channel AHD video input, adjustable display of single and two-segment images and picture-in-picture images, Full images/2 images adjustable, Supports AHD720P/960P/1080P and

SELLING POINTS & NOTES

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- **With lock button**:** Important videos can be locked with one click. After locking, they will not be overwritten or deleted by loop (useful
- There is a **24-hour parking monitoring** version: with constant power supply, continuous monitoring can also be done during parking
- 706 physical keys (706KEY) operation, can be pressed even with gloves
- The menu language can be custom: Chinese/Russian version is available (default Chinese)
- Support mirror/original image switching, reversing ruler line
- **Input DC12-36V:** universal for 12V / 24V models

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

IN DETAIL

Product Views & Applications

TYPICAL APPLICATIONS

Trucks & Trailers | Buses & Coaches | Forklifts | Vans & Light Commercial | Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.