



JPM-708

9 Inch 2 Channel Mirror Touch Battery AI AHD Monitor

180 x 121 | 85° | TFT LCD with LED backlight | 9 inch

With touch power switch

With light-sensing function

Reverse trigger

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- Touch screen + touch power switch (the biggest difference between this model and 706)
- The panel is made into a touch screen, and menus can be clicked directly on the screen without mechanical buttons
- With touch power switch: turning on/off is done on the touch panel, no additional power button is needed
- No mechanical keys = no problems with key wear, water ingress, or key jamming, making long-term use more worry-free
- The touch panel is flat and easy to scrub, and dirt and oil stains will be clean with just one wipe
- 7-inch car display, single-channel image

TECHNICAL SPECIFICATION

Display Size	9 inch
Viewing Angle	85°
Channels	2 channels
Image Mode	Mirror image
Power Supply	DC 12-36 V
Connector	(Optional) RCA / BNC / 4pin connector
Resolution	180 x 121
Display	TFT LCD with LED backlight
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

ORDERING REFERENCE / AVAILABLE VARIANTS

7"i9"10.1"nchAHDmonitorwithtouchbuttons(Detachablesunshade) 1.AV Resolution: 1024*R.G.B*600 2.Back Light Luminance: LED, 600-700 cd/m2 3.View angle: L/R:85°, UP:85°, down:85° degree 4.2 channel AHD video input, 2 ways Trigger priority: V2 > V1 5.Audio Input: Built-in speaker, 1 way audio input (V2) 6.Support: AHD720P/960P/1080P (CVBS/TVI) input 7.OSD menu: Reverse ruler line, mirror

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Supports CVBS and AHD cameras, both old and new cameras can be connected
- With light-sensing function: automatically adjusts the screen brightness according to the ambient light
- Brightness and contrast can be adjusted in the touch menu
- You can switch the mirror image/original image of the picture in the menu without changing the camera or changing the cable
- 1 video input, supports CVBS / AHD
- **Reverse trigger:** Automatically switch to reverse screen when engaging reverse gear

ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

Trucks & Trailers

Buses & Coaches

Forklifts

Vans & Light Commercial

Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.