


# JPM-709

## 7 Inch 3 Channel Mirror Battery AI AHD Monitor

180 x 121 | 85° | TFT LCD with LED backlight | 7 inch

**Adjustable reversing guide lines** **Connector options**

**Shenzhen Jifuan Intelligent Technology Co., Ltd.**
Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.*

**+86 188 7400 7838 (WhatsApp / WeChat)**
**info@jfacam.com**
www.jfacam.com | www.antuvision.com

OVERVIEW

# Key Features & Specifications

## KEY FEATURES

- 3-channel monitor with split and full screen modes
- AHD / CVBS input, separate trigger per channel
- Wide voltage for 12V / 24V vehicles
- For trucks and buses needing 3 camera views (rear + 2 sides)
- Wide 85 degree viewing angle covers blind spots around the vehicle
- Mirror / normal image selectable to match camera position

## TECHNICAL SPECIFICATION

| | |
|---|---|
| **Display Size** | 7 inch |
| **Channels** | 3 channels |
| **Viewing Angle** | 85° |
| **Image Mode** | Mirror image |
| **Power Supply** | DC 12-36 V |
| **Connector** | (Optional) RCA / BNC / 4pin connector |
| **Resolution** | 180 x 121 |
| **Display** | TFT LCD with LED backlight |
| **Video Input** | AHD / CVBS, 1ch or multi-channel (per model) |
| **Housing** | Vehicle-mounted housing with bracket |
| **Ordering** | Full parameter sheet available on request |

### ORDERING REFERENCE / AVAILABLE VARIANTS

7"inch AHD 3ch in, 3pcs trigger cable vehicle mounted display (Detachable sunshade) 1.AV Resolution: 1024R.G.B600 2.Back Light Luminance: LED, 600-700cd/m2 (7") 3.View angle: L/R:85°, UP:85°, down:85° degree 4.3 channel AHD video input, 3 ways Trigger priority: V2 > V1 > V3 5.Audio Input: Built-in speaker, 1 way audio input (V2) 6.Support: AHD720P/960P1080P (CVBS/TVI) input 7.OSD

SELLING POINTS & NOTES

# Selling Points, Ordering & Usage Notes

## PRODUCT SELLING POINTS

- Adjustable reversing guide lines
- Built-in speaker with audio input
- Auto trigger switching shows the reversing view instantly
- Wide 12-36V vehicle power input with protection
- **Connector options:** RCA / 4-pin aviation / BNC

## ORDERING NOTES

- **Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- **Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- **Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- **Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- **Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

## USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

**Shenzhen Jifuan Intelligent Technology Co., Ltd.**

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors, cable length and firmware available on request.*

**+86 188 7400 7838 (WhatsApp / WeChat)**

**info@jfacam.com**

www.jfacam.com | www.antuvision.com

IN DETAIL

## Product Views & Applications





### TYPICAL APPLICATIONS

Trucks & Trailers | Buses & Coaches | Forklifts | Vans & Light Commercial | Fleet & MDVR Systems

### CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.