



JPM-711

Universal Monitor

TFT LCD with LED backlight

Viewing angle range

PAL / NTSC auto switching

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- Adopting the public version 1016 platform: the same specifications are more cost-effective, suitable for volume orders and fleet projects
- It has all the necessary functions: single-screen display, automatic reversing switching, reversing reference line, wide-voltage power supply
- Shipping is stable and orders can be returned for a long time
- Resolution 1024 x R.G.B x 600, clear picture
- **Viewing angle range:** left/right 85°, up 85°, down 85°
- Dimensions 220 x 107.2 x 15mm (including 33mm bracket): ultra-thin and low, can be installed on the instrument panel and takes up no space

TECHNICAL SPECIFICATION

Display	TFT LCD with LED backlight
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Power Supply	DC 12-36V wide voltage
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

ORDERING REFERENCE / AVAILABLE VARIANTS

QTY: 10PCS G.W: 10.3KG Size: 55.5*46*17CM

Product Views & Applications



TYPICAL APPLICATIONS

Trucks & Trailers

Buses & Coaches

Forklifts

Vans & Light Commercial

Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.