



JPM-906Q

9 Inch 4 Channel Monitor

TFT LCD with LED backlight

Four AHD inputs**

12 split modes**

PAL / NTSC auto switching

OSD menu

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Key Features & Specifications

KEY FEATURES

- 9-inch screen, resolution 1024 x R.G.B x 600
- **Four AHD inputs****: full screen/2 pictures/3 pictures/4 pictures adjustable; supports AHD 720P/960P/1080P and CVBS mixed input
- **12 split modes****: can be cut into two, three or four parts, H-shaped arrangement, each screen can be displayed independently
- PAL / NTSC auto switching
- Four-way trigger, priority order **V2 > V1 > V3 > V4**:
Automatically switch to the corresponding screen when engaging reverse gear/turning
- 4 channels can independently adjust the left and right/up and down flip mirror: side view, rear view, and front view can be adjusted with one machine

TECHNICAL SPECIFICATION

Display	TFT LCD with LED backlight
Video Input	AHD / CVBS, 1ch or multi-channel (per model)
Power Supply	DC 12-36V wide voltage
Housing	Vehicle-mounted housing with bracket
Ordering	Full parameter sheet available on request

Product Views & Applications



TYPICAL APPLICATIONS

Trucks & Trailers

Buses & Coaches

Forklifts

Vans & Light Commercial

Fleet & MDVR Systems

CUSTOMISATION AVAILABLE

- **Video system:** AHD 720P / 1080P or CVBS, PAL & NTSC - confirmed per order.
- **Connector:** 4-pin aviation / RCA / waterproof plug, with matching cable.
- **Cable length and pinout:** standard pigtail; 1 m / 5 m / 10 m or custom.
- **Image mode:** mirror or non-mirror image, with or without parking lines.
- **Branding:** neutral or customer-branded packaging.