



MDVR-708C-1080P

8ch 1080n Mobile Dvr

1 / 2 / 3 / 4 / 8 channels | Size | Interface:

Storage

Built-in supercapacitor

Smart power management

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China

OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

OVERVIEW

Key Features & Specifications

KEY FEATURES

- 8-channel mobile DVR with 2.5 inch hard disk / SSD storage
- Built-in Hisilicon high-performance image processor, H.265 standard (about half the storage of H.264) with H.264 also supported
- 8CH 1080N AHD / TVI / CVI / CVBS + IPC five-in-one video input, strong compatibility
- 8+1 real-time preview and storage; 1, 2, 3, 4, 9 split display
- 1 CH synchronized AV output + 1 CH VGA output
- **Storage:** 2.5 inch HDD / SSD up to 2TB, plus 1 SDXC card up to 256GB (English SPEC lists 512GB, to be confirmed)

TECHNICAL SPECIFICATION

Transmission	Interface:
Audio	Image resolution 1080N/720P /960H/D1/CIF
Recording	mode Automatic/Alarm
Playback	Video inquiry Inquiry by channel/Recording type/Alarm Type
Alarm Output	input 4 digital inputs
Power Supply	input 9~32V DC
Power Consumption	Standby 4mA/12V
Storage	Size
Channels	1 / 2 / 3 / 4 / 8 channels (per model)
Connectivity	4G, GPS, WiFi, ADAS / DMS optional
Video Input	AHD 1080P / 720P, IPC supported

ORDERING REFERENCE / AVAILABLE VARIANTS

8ch mdvr support 2ch IPC camera support : 1080p camera support 2TB+256SD Support 4G +GPS+wifi (optional) Power input power: 8-36V; Output voltage: 12V/2A; Working temperature -20°C--60°C default VGA video out | 1080p, without 4g gps wifi

Selling Points, Ordering & Usage Notes

PRODUCT SELLING POINTS

- Automatic hard disk heating for cold-start conditions
- Built-in supercapacitor:** no data loss or disk damage on abnormal power outage
- Special file management with data encryption; proprietary bad-track detection keeps recording continuous and extends disk life
- Wide voltage DC 8-36V / 9-32V professional vehicle power design with under-voltage, short-circuit and reverse-connection protection
- Smart power management: low-voltage shutdown, low consumption after flame-out
- Built-in G-sensor for real-time monitoring of vehicle driving behaviour

ORDERING NOTES

- Video system:** confirm AHD 720P / 1080P or CVBS, and PAL / NTSC before ordering.
- Image mode:** confirm mirror or non-mirror image, and whether parking guide lines are required.
- Connector:** confirm 4-pin aviation or RCA, plus cable length (standard 0.3-0.5 m pigtail; 1 m / 5 m / 10 m available) and pinout for your harness.
- Lens angle and mounting position: confirm the required angle and where the camera is fitted (side / rear / front / cabin).
- Voltage:** confirm your vehicle system - 12V and 24V versions are both available.
- Quantity, packing (colour box / neutral box) and printing or logo requirements.
- Mounting bracket:** confirm the bracket type and screw thread your vehicle needs.
- Default specification has no parking guide lines. Other angles, NTSC or mirror versions must be confirmed in advance.

USAGE & PRECAUTIONS

- Check the supply voltage and polarity before connecting power; wrong wiring can damage the camera.
- Keep the waterproof connector tight and seal the joint; do not cut or extend the pigtail.
- Route the cable away from heat sources, sharp edges and moving parts, and secure it with clips.
- Clean the lens and the IR window with a soft cloth only; avoid high-pressure washing directly at the lens or connector.
- Do not open the sealed housing - doing so voids the waterproof rating and the warranty.
- A dirty lens or IR window reduces night image quality, so check them during regular maintenance.

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street,
Longhua District, Shenzhen, China
*OEM & ODM welcome - custom logo, packaging, connectors,
cable length and firmware available on request.*

+86 188 7400 7838 (WhatsApp / WeChat)

info@jfacam.com

www.jfacam.com | www.antuvision.com

Product Views & Applications



TYPICAL APPLICATIONS

- Fleet Telematics
- Trucks & Trailers
- Buses & Coaches
- Taxis & Ride-Hailing
- Insurance & Evidence

CUSTOMISATION AVAILABLE

- Channels and camera type:** confirm 1 / 2 / 3 / 4 / 8 channels and camera model.
- Storage:** SD card or 2TB SSD / HDD; confirm recording days required.
- Connectivity:** 4G, GPS, WiFi, ADAS / DMS - confirmed per order.
- Platform:** confirm whether our CMSV platform is required (license cost separate).
- Branding:** neutral or customer-branded packaging and labels.

Options, Packing & Why Jifuan

PACKING & DELIVERY

- **MOQ:** flexible, from 50-100 pcs per model for standard items (mixing allowed).
- **Lead time:** 3-20 working days after deposit, depending on quantity and stock.
- **Packing:** individual white / colour box, master carton with buyer label.
- **Terms:** FOB Shenzhen; T/T, PayPal or Western Union.
- **Warranty:** 12 months from shipment against manufacturing defects.
- **Samples:** available for evaluation before mass production.

QUALITY CONTROL

- 100% ageing test before packing: every unit runs on a burn-in rack.
- **Waterproof test:** IP67 / IP68 / IP69K pressure and immersion checks on sealed models.
- High & low temperature chamber: -20C to +70C operating verification.
- Vibration and shock test for truck, bus and off-highway applications.
- **Full-function check:** video output, IR switching, connector and cable continuity.
- 1-year warranty with responsive technical support and spare-parts supply.

WHY BUY FROM JIFUAN

- **Supply chain integration:** cameras, monitors, MDVR and 360 systems matched from a vetted supplier network - one contact, one shipment.
- **Product experience:** 15+ years on vehicle video, so the platform that fits your vehicle and budget is the one we recommend.
- **Project experience:** fleet, bus, trailer and off-highway builds supplied with the brackets, cables and connectors the vehicle actually needs.
- **Customisation:** housing colour, logo, bracket, connector, cable length, lens angle and firmware changed to suit your market, with a fast answer on feasibility.

Contact us for a quotation

Shenzhen Jifuan Intelligent Technology Co., Ltd.

Building 9, West District, Zhangge Community, Fucheng Street, Longhua District, Shenzhen, China

+86 188 7400 7838 (WhatsApp / WeChat) **info@jfacam.com**