Video output forma	DIP Schema	DIP Schematic Diagram				
Video output format	1	2	All are "OFF"			
AHD or TVI	OFF	ON	hasha			
HDMI	ON	ON				
VGA	ON	OFF	All are "ON			
The format is determined by menu selection or serial port protocol	OFF	OFF				
	Resolution	dialing rules				
Resolution	3	4	5	6		
800*480	ON	ON	ON	ON		
960*480	OFF	OFF	OFF	OFF		
1024*480	OFF	ON	OFF	ON		
1280*480	ON	ON	OFF	ON		
1280*540	OFF	ON	ON	OFF		
1440*540	ON	ON	ON	OFF		
800*600	OFF	OFF	ON	OFF		
1024*600	OFF	OFF	OFF	ON		
1280*640	ON	OFF	OFF	ON		
1280*720	ON	ON	OFF	OFF		
1540*720	ON	OFF	ON	ON		
1920*720	OFF	ON	ON	ON		
1920*1080	ON	OFF	ON	OFF		
AV_NTSC	ON	OFF	OFF	OFF		
AV_PAL	OFF	OFF	ON	ON		
AHD_720P_25frame	ON	ON	ON	ON		
AHD_720P_30frame	ON	ON	OFF	ON		
AHD_1080P_25frame	ON	ON	ON	OFF		
AHD_1080P_30frame	ON	ON	OFF	OFF		
TVI_1080P_25frame	OFF	ON	ON	ON		
TVI_1080P_30frame	OFF	ON	OFF	ON		
TVI_720P_25frame	OFF	ON	ON	OFF		
TVI_720P_30frame	OFF	ON	OFF	OFF		
note:						

1.The dial code is in the "OFF" position by default

2.If all 6 bits are OFF, the video output is determined by the menu or the serial port protocol

视频输出格式	拔码示意图			
拨码位置 拨码规则 迟频输出格式	1	2	全为 [111]	
HD或者TVI	OFF	ON		
DMI	ON	ON	全为 '	ON"
GA	ON	OFF	11111	
式由菜单选择或串口发协 2次定	OFF	OFF		
分别	摔率拔	码规则		
拨码位置 一	3	4	5	6
00*480	ON	ON	ON	ON
60*480	OFF	OFF	OFF	OF
24*480	OFF	ON	OFF	ON
80*480	ON	ON	OFF	ON
0*540	OFF	ON	ON	OFF
80*540	OFF	ON	OFF	OFF
40*540	ON	ON	ON	OF
0*600	OFF	OFF	ON	OF
24*600	OFF	OFF	OFF	ON
80*640	ON	OFF	OFF	ON
30*720	ON	ON	OFF	OFF
40*720	ON	OFF	ON	ON
20*720	OFF	ON	ON	ON
	ON	OFF	ON	OFF
20*1080	ON	OFF	OFF	OFF
NTSC	OFF	OFF	ON	ON
_PAL D 720D 25帧	ON	ON.	ON	ON
D_720P_25帧 D_720P_30帧	ON	ON	OFF	ON
D_1080P_25帧	ON	ON	ON	OFF
D_1080P_30帧	ON	ON	OFF	OFF
_1080P_25帧	OFF	ON	ON	ON
[_1080P_30帧	OFF	ON	OFF	ON
	OFF	ON	ON	OFF
		ON	OFF	OFF