

7" Inch AHD Quad Waterproof Monitor



Specifications	Model number: JPM-718QW
Screen Ratio(BOE IPS)	7"high digital new panel ,16:9image
Back Light Luminance	LED500-650cd/m ²
Resolution	1024xRGBx600
View angle (standard)	Hor. L/ R(85)Ver. UP/DOWN(85)Full perspective
AV Inputs	Supports 4 HD camera inputs(1080P@30fps / 1080P@25fps / 720P@30fps / 720P@25fps), Quad-view display supported(CVBS&AHD)
Number of Trigger and display	4 ways Trig functionTrigger priority:V2>V1>V3>V4
Multiple modes	Single, dual, triplex, quad, trefoil, Y-split and PIP image display
Backlight brightness	with light sensor receiver,can adjust screen brightness automatically day & night
Compatible system	NTSC & PAL (automatically)
OSD control	Color, Brightness, Contrast, Volume, Language (English, Chinese,Spanish)
Power requirement	Automobile storage battery (12-36V) /output, 12V
Power consumption	5.5W
Working temperature	-20°C to 70°C
Storage temperature	-30°C to 80°C
Waterproof grade	IP69k
with shock resistance of	5.9G
Materials/Key color	Metal housing ,Detachable sunshade&Metal U type bracket
Size	188*127.2*34(79)mm
MontiorAnd Camera Connector	RCA/ 4pin connector (Optional)
Accessories	Remote controller, Power supply cable , User manual, Metal U type bracket