



Model No.	JFD-W2
vehicle type	fit motorcycle
system	Android 8.1 2+32g
communication protocol	JT808/1078
API available	can support if you want to integrate it to your platform
lens quantity	2 cams or 3 cams for optional
video quality	2 lens (1080+1080P)@25fps
	3 lens (1080+720+720P)@25fps
video format	TS H.264
view angle	90 degree for the 3 cams
cameras install	separate install from the main dash cam body
picture format	JPEG
4G network	Asia version: FDD LTE B1 B3 B5
	America version: FDD LTE B2 B4 B5 B7 B8 B12
Wifi hot spot	support
serial port	TTL to RS232/485 for extra device connection
tracking platform	cmsv6
power supply	5-9V
waterproof standard	IP68
working current	0.8A
sleep current	5mA
working temperature	-20-75℃
storage temperature	-20-80℃

function on the cmsv6 tracking platform	
Geo fence	support
live streaming	support
intercom	support
remote set server IP	support
capture picture	support
GPS tracking	support
driving history check	support
overspeed alarm	support
event alarm to platform	support
SOS button alarm	support
4g traffic set	support
collision alarm	support
text to voice broadcast	support
remote set time & date	support
plate license on video mark	support

Package content	1xw2 dash cam 2x cameras 2x 3m cables for cameras 1x power cable 1xGPS antenna 1x sos button 1x user manual
unit weight/PCS	0.85KG
quantity/carton	30PCS
weight/carton	25.5KG